


Fig.IN 172

PN10 rechte GG-25 terugslagklep, scharnierende klep, bronzen Rg5 dichting, flenzen en boring PN10, Fig.IN 172.

PN10 swing type check valve, cast iron GG-25 body and bolted cover, bronze Rg5 seats, flanged PN10, Fig.IN 172.



**OPMERKINGEN / REMARKS**

**MATERIAAL / MATERIAL**

Huis / Body	Gietijzer / Cast iron	GG-25	GLJ-250	JL-1040 / 0.6025
Deksel / Bonnet	Gietijzer / Cast iron	GG-25	GLJ-250	JL-1040 / 0.6025
Zitting / Seat	Bronz / Bronze	Rg 5	CuSn5Zn5Pb5-C	CC491K / 2.1096.01
Klep / Disc	Nodulair gietijzer / Nodular cast iron	GGG-40.3	GJS-400-18 LT	JS-1025 / 0.7043
As / Shaft	Messing / Brass	Ms58	CuZn39Pb3	CW614N / 2.0401

**AFMETINGEN / DIMENSIONS**

DN	40	50	65	80	100	125	150	200	250	300	350	400	500	600						
L	180	200	240	260	300	350	400	500	600	700	800	900	1100	1300						
ØD	150	165	185	200	220	250	285	340	395	445	505	565	670	780						
H	100	105	120	145	155	165	190	290	300	365	420	485	580	700						
PCD	110	125	145	160	180	210	240	295	350	400	460	515	620	725						
nxd	4x18	4x18	4x18	8x18	8x18	8x18	8x22	8x22	12x22	12x22	16x22	16x26	20x26	20x30						
Kilo	9	12	15	22	28	42	54	86	160	210	360	505	990	1187						